

TRIBOGLIDE X

PRODUCT DATA

PRODUCT DESCRIPTION

Neptune TriboGlide X is a drilling and completions fluid lubricant additive that provides coiled tubing lubrication and ROP enhancement in medium to high brine aqueous fluids. Recommended dose for treatment is 1.5% to 3% of total sweep fluid volume to achieve a 50% reduction in friction coefficients. Perform compatibility tests and review the SDS prior to use.

FEATURES

- Establishes a strong film on metal surfaces to aid in lubrication
- Tolerant of the harshest of brines in the field
- Will not grease out in high brines
- Low foaming tendencies
- pH tolerant from 5 - 10

PROPERTIES

- Physical: amber liquid
- Solubility (water): dispersible
- Density (lb/gal): 7.6 ± 0.15
- Pour point (°F): < -20
- Flash point (°F): > 240

SAFETY

- Health: 2
- Fire: 1
- Physical hazard: 0
- DOT: Not regulated



Because the conditions of use of this product are beyond the seller's control, the product is sold without warranty either expressed or implied and upon condition that purchaser make its own test to determine the suitability for purchaser's application. Corrosion can not be entirely prevented. Manufacturing methods employed coiled tubing manufacturers may affect asset and chemical performance. Purchaser assumes all risk of use and handling of this product. This product will be replaced if defective in manufacturing, packaging or if damaged. Except for such replacement, seller is not liable for any damages caused by this product or its use. The statements and recommendations made herein are believed to be accurate. No guarantee of their accuracy is made, however. ©2024 Neptune Chemical Corporation, LLC. All Rights Reserved.